



## Emergency luminaire Art.-No.: WER029-E

LED emergency luminaire for wall installation and for the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 605982-22 and DIN EN 1838. This recessed luminaire is designed for installation in conventional jacks. The mounting frame can be aligned with the jack. The zinc-aluminum cover is locked without externally visible fastening. Through the status LED which is incorporated in the lens the harmony of the housing is not interrupted.



### TECHNICAL DATA

|                                     |                             |
|-------------------------------------|-----------------------------|
| Luminaire type                      | Emergency luminaire         |
| Mounting                            | Recessed wall               |
| Pictograph                          | No                          |
| Illuminant                          | LED                         |
| Housing material                    | Zinc die-cast               |
| Colour                              | Stainless steel look        |
| Mechanical rating IP                | 20                          |
| Impact resistance IK                | ≥ 3                         |
| Protection class                    | 2                           |
| Supply                              | Central power supply system |
| Monitoring                          | None                        |
| Operation time                      | CPS                         |
| Operation mode                      | Maintained mode             |
| Input Voltage AC                    | 230 V                       |
| Input Frequency Hz                  | 50 / 60 Hz                  |
| Input Voltage DC                    | 100-254 V                   |
| Power consumption max.              | 1,9 W                       |
| Power consumption maintained        | 1,9 W                       |
| Power consumption non-maintained    | 0 W                         |
| Ambient temperature maintained mode | -20 °C / 40 °C              |



|   |                |
|---|----------------|
| Ambient temperature non-maintained mode | -20 °C / 40 °C |
| Length                                  | 20 mm          |
| Width                                   | 90 mm          |
| Height                                  | 90 mm          |
| Install. dim. diameter                  | 68 mm          |
| Weight                                  | 0.3 kg         |
| Weight incl. Packaging                  | 0.33 kg        |
| Connection cross-section                | 1.5 mm         |
| Switching input L'                      | No             |
| Emergency light blocking                | No             |
| Battery connector                       | None           |
| Dimming function                        | No             |
| Luminous flux mains mode                | 140 lm         |
| Luminous flux emergency mode            | 140 lm         |
| Customs tariff number                   | 94056180       |
| Country of origin                       | Germany        |
| EAN                                     | 4260682147363  |



**TECHNICAL DRAWING**

