



Art.-Nr: XPXU413SC
Emergency light Self-contained
Universal, SelfControl (SC), 3 h, , IP66, Aluminum die-cast,
Glass, Yellow (RAL 1003)



Polycarbonate cylinder safety luminaire with explosion protection for gas and dust Ex zones.

Prepared for two cable entries for feed-through wiring. By attaching a pictogram, can also be used as an emergency exit sign luminaire.

By means of mounting adapter for wall/ceiling mounting or suspension by means of eye bolt.

Labelling according to 2014/34/EC (ATEX)

Zone 1 / zone 21 gas and dust

- Ex d IIB T6 Gb / Ex d IIB T6 Gb
- Ex t IIIC T85°C Db

Manufactured in accordance with

-EN 60079-0:2018, EN 60079-1:2014, EN 60079-31:2014

-Certified by INERIS 20ATEX0005X

Automatic monitoring of safety luminaire with SelfControl.



More information

www.rp-group.com/en/item/XPXU413SC



TECHNICAL DATA


Luminaire type	Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminum die-cast, Glass
Housing color	Yellow (RAL 1003)
Protection type (IP)	IP66
Impact resistance (IK)	10
Certification	WEEE, CE, Explosion-protected
Insulation class	1
Supply	Self-contained
Monitoring	SelfControl (SC)



Bridging time	3 h
Battery	LiFePO4 3,2 V/
Operating mode	Non-maintained / maintained
Input voltageAC	230 V
Input frequency	50 / 60 Hz
Power max.	45 W
Power maintained	38,5 W
Ambient temperature maintained mode	0 °C to 50 °C
Ambient temperature non-maintained mode	0 °C to 50 °C
Depth	1360 mm
Width	157 mm
Height	197 mm
Weight	5.5
Weight incl. packaging	6.7
Connection cross-section	2.5 mm ²
Switching input	No
Emergency light blocking	Yes
Battery connection	Clip
Dimming function	No
Luminous flux mains	5550 lm
Luminous flux emergency	980 lm
Customs tariff number	94051190
EAN	4262483026922



TECHNICAL DRAWING



ACCESSORY LIST

X-K0001 -
X-MB001 -
X-KE001 -
X4N -

As of: 11.06.2025 - Subject to technical changes and errors.