



**Art.-No.: YEDRA-REWD-2301**  
**LED recessed downlight "RAVIO", round, 172x80mm, 23W, 2400lm, 3000K, CRI >80, IP44, Dali dimmable**

LED recessed and surface-mounted downlight, RAVIO series. IP20 (for the surface-mounted version). Housing made from plastic (PC) and passive aluminium cooler. Diffuser made from plastic, opal. Operating unit can be switched or dimmed (DALI dimmer), external (integrated in the surface-mounted version). Version with Casambi Bluetooth control available. DC compatibility on request.



### DANE TECHNICZNE


Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0,95
System power	23 W
Inrush current	5 A
Inrush current duration	50 µs
Luminaire on B10A fuse	30 Stk.
Luminaire on B16A fuse	50 Stk.
Luminaire on C10A fuse	50 Stk.
Luminaire on C16A fuse	83 Stk.
Connection cross section	1,5 mm <sup>2</sup>
Dimming	DALI
Electrical version	with internal operating device, dimmable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	3 000 K
Rated luminous flux	2 400 lm
Luminous efficacy	104 lm/W
Light colour	830
Colour rendering index (CRI)	> 80
Colour tolerance	3
Beam angle	64,2/64,4 °
Lifetime (h, at 25°C)	50 000 h, L80



Acceptance tests	
Certifications	CE, ENEC
Protection class	II
Ingress protection (IP) rating	IP 44
Glow wire test	650° C
Ambient temperature	0 to +25 C°
Physical data	
Mounting method	recessed ceiling mounted
Housing material	Aluminium
Housing colour	white
Cover material	PC
Height (H)	80 mm
Diameter $\varnothing$	172 mm
Ceiling Cut-out $\varnothing$	160 mm
Product weight	0,6 kg
Weight incl. Packaging	0,7 kg
Packaging Length (L)	190 mm
Packaging Width (B)	190 mm
Packaging Height (H)	145 mm



**LIGHT DISTRIBUTION**



cd/klm

— C0 - C180 — C90 - C270

$\eta = 100\%$