




Art.-Nr: YMOCA-A2D CASAMBI® A2D Bluetooth control module

YMOCA A2D can control one or two 0–10 V controllable LED drivers or one driver for white (TW) LED applications with two 0–10 V control interfaces where the colour temperature can be controlled. The controller can also be configured to DALI mode. In this mode, it can control a DALI LED driver and/or be connected to a DALI sensor for presence detection and daylight control.



More information www.rp-group.com/en/item/YMOCA-A2D



TECHNICAL DATA

| Dimensional | |
|---------------------------------|-------|
| Dimensions | |
| Product dimensions Length | 76 |
| Product dimensions Width | 26 |
| Product dimensions Height | 23 |
| Product weight | 0.04 |
| Color | |
| Color | White |
| Storage temperature range | |
| Storage temperature range (Min) | -25 |
| Storage temperature range (Max) | +70 |
| Housing temperature | |
| Housing temperature (Max) | 70 |
| Temperatures | |
| Ambient temperature (Min) | -20 |
| Ambient temperature (Max) | +45 |
| CASAMBI Products | |





| Consumption in standby mode | 0.5 W |
|-----------------------------|-------------------|
| Dimming function | DALI, 0-10V |
| Communication type | CASAMBI |
| Frequency band | 2,403 - 2,479 GHz |
| Max. transmission power | +4 dBm |
| DALI bus supply | Yes |
| DALI bus voltage | 12V DC |
| DALI output current | 20 mA |
| CASAMBI Repeater | Yes |
| Protection type (IP) | IP20 |
| Certifications | CE, RoHS |

As of: 15.04.2025 - Subject to technical changes and errors.