



## Art.-Nr: YMOCA-RELAIS-LR CASA relay, 2-way potential-free

The relay has 2 potential-free contacts. The maximum power stated below can be switched for each contact. What's more, both contacts can be controlled independently of one another. With the additional "long-range" feature, you can now also enjoy reliable control from even greater distances.



More information

[www.rp-group.com/en/item/YMOCA-RELAIS-LR](http://www.rp-group.com/en/item/YMOCA-RELAIS-LR)



### TECHNICAL DATA

Dimensions	
Product dimensions Length	143 mm
Product dimensions Width	38 mm
Product dimensions Height	23 mm
Product weight	0.03 kg
Color	
Color	White
Housing material	
Housing material	Polycarbonate
Storage temperature range	
Storage temperature range (Min)	-25 °C
Storage temperature range (Max)	+75 °C
Housing temperature	
Housing temperature (Max)	60 °C
Electrical connection	
Supply	Mains
Connection cross-section	1.5 mm <sup>2</sup>
power supply	
Electrical design	Switchable
Temperatures	
Ambient temperature (Min)	-20 °C
Ambient temperature (Max)	+50 °C



CASAMBI Products	
Max. Output voltage DC	28 V
Consumption in standby mode	0.15 W
Load types	Ohmic load
Switching output	1500 VA
Switching cycles	50000 pcs.
Communication type	CASAMBI
Frequency band	2,403 - 2,479 GHz
Max. transmission power	+8 dBm
CASAMBI Repeater	Yes
Protection type (IP)	IP20
Certifications	CE, RoHS
Mounting	
Mounting	Ceiling mounting

As of: 15.04.2025 - Subject to technical changes and errors.