



## Art.-No.: YMOCA-RELAIS Casa Relais 2-way potential-free switching

The relay has 2 potential-free contacts. The max. power specified below can be switched for each contact. Furthermore, both contacts can be controlled independently of one another.



### TECHNICAL DATA

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Consumption standby	0.15 W
Output max.	1,500 VA
Output voltage AC max.	250 V
Output voltage DC max.	28 V
Connection cross section	1.5 mm <sup>2</sup>
Switch cycles	50,000
Load types	Ohmic load
Communication type	Bluetooth
Electrical version	with internal operating device
Switching output	1,500 VA
Frequency band	2,403 - 2,479 GHz
max. transmission power	+4 dBm
CASAMBI Inside	Yes
Acceptance tests	
Certifications	CE, ROHS
Protection class	II
Ingress protection (IP) rating	IP 20
Ambient temperature	-20 to +50 C°
Storage temperature	-25 to +75 C°
Housing temperatur max., tc	60 C°



Physical data	
Mounting method	recessed ceiling mounted, recessed wall mounted
Housing material	Polycarbonate
Housing colour	white
Length (L)	143 mm
Width (B)	38 mm
Height (H)	27 mm
Product weight	0.03 kg