



Art.-Nr: YMOCA-ROLLO-MINI-LR CASA ROLLO Mini

NEW PRODUCT! NOW AVAILABLE!

The CASA ROLLO Mini module has been developed especially for flush-mounted installation. It gives you a convenient way of controlling roller shutters, blinds or awnings via a push button or the practical app. With the additional "long-range" feature, you can now also enjoy reliable control from even greater distances.



More information

www.rp-group.com/en/item/YMOCA-ROLLO-MINI-LR



TECHNICAL DATA

Dimensions	
Product dimensions Length	50 mm
Product dimensions Width	48 mm
Product dimensions Height	30 mm
Packaging dimensions	
Packaging dimensions Length	60 mm
Packaging dimensions Width	60 mm
Packaging dimensions Height	34 mm
Weight incl. packaging	0.1 kg
Certification	
Protection type (IP)	IP20
Storage temperature range	
Storage temperature range (Min)	-25 °C
Storage temperature range (Max)	+75 °C
Housing temperature	
Housing temperature (Max)	60 °C
Electrical connection	
Connection cross-section	1.5 mm ²



power supply	
Electrical design	Switchable
Temperatures	
Ambient temperature (Min)	-20 °C
Ambient temperature (Max)	+50 °C
CASAMBI Products	
Input voltage AC	230 V
Consumption in standby mode	0,5 W
Load types	Inductive load
Switching output	345 VA
Communication type	CASAMBI
Frequency band	2,403 - 2,479 GHz
Max. transmission power	+8 dBm
CASAMBI Repeater	Yes
Push-button connection	2
Protection type (IP)	IP20
Certifications	CE, RoHS

As of: 15.04.2025 - Subject to technical changes and errors.