



Art.-Nr: YMOCA-SAL-1064

Salvador 1032

It can manage up to 32 DALI driver addresses

The Salvador 1000 series seamlessly integrates DALI-wired devices into the Casambi system. Once integrated, DALI devices appear as virtual devices in the Casambi network.

This product supports industry standards such as DALI D4i, DALI DT6, and DALI DT8.

When designing lighting control systems, it is important to note that DALI controls, such as switches and sensors, should not be connected to the products of the Salvador 1000 series.

An external power supply is required for the DALI bus to operate the Salvador 1000 series.



More information

www.rp-group.com/en/item/YMOCA-SAL-1064



TECHNICAL DATA

Dimensions	
Diameter	40,4 mm
Product dimensions Length	36,3 mm
Product dimensions Width	14 mm
Product dimensions Height	15 mm
Product weight	15 g
Packaging dimensions	
Packaging dimensions Length	170 mm
Packaging dimensions Width	110 mm
Packaging dimensions Height	20 mm
Weight incl. packaging	50 g
Color	
Color	White
Storage temperature range	
Storage temperature range (Min)	-20 °C
Storage temperature range (Max)	+75 °C
Housing temperature	



Housing temperature (Max)	+65 °C
Temperatures	
Ambient temperature (Min)	-20 °C
Ambient temperature (Max)	+55 °C
CASAMBI Products	
External power supply unit	DALI Power Supply
Consumption in standby mode	0,2 W
Communication type	Bluetooth, CASAMBI, DALI 1, DALI 2
Frequency band	2,403 - 2,479 GHz
Max. transmission power	+8 dBm
DALI bus supply	External
DALI bus voltage	9,5 - 22,5 VDC
DALI output current	max. 250 mA
Number of DALI addresses	64 pcs.
CASAMBI Repeater	Yes
Certifications	CE

As of: 15.04.2025 - Subject to technical changes and errors.