



**Art.-Nr: YMOCA-TED
CASAMBI®TED module
trailing edge dimming for dimmable LEDs /**

The CBU-TED module is a Bluetooth-controlled CASAMBI®trailing-edge dimmer that enables all available illuminants to be continuously dimmed. It can also be used to switch luminaires on and off, and can be installed behind a conventional light switch, in a luminaire or in a terminal box.



More information
www.rp-group.com/en/item/YMOCA-TED



TECHNICAL DATA

Dimensions	
Product dimensions Length	40.4 mm
Product dimensions Width	36.3 mm
Product dimensions Height	14 mm
Product weight	15 g
Color	
Color	White
Housing material	
Housing material	Polycarbonate
Certification	
Certification	CE
Insulation class	2
Protection type (IP)	IP20
Storage temperature range	
Storage temperature range (Min)	-25 °C
Storage temperature range (Max)	+75 °C
Housing temperature	
Housing temperature (Max)	65 °C
Electrical connection	
Connection cross-section	1.5 mm ²



Switching output	100 W
Type of dimming	TRIAC, CASAMBI
System performance	100 W
Input voltage AC	220-240V / 50-60Hz V
Starting current	10 A
Consumption standby	0.3 W
Starting time	100 ms
Temperatures	
Ambient temperature (Min)	-20 °C
Ambient temperature (Max)	+45 °C
CASAMBI Products	
Communication type	Bluetooth
Max. transmission power	+4 dBm

As of: 10.04.2025 - Subject to technical changes and errors.