



Art.-No.: YTUVA-LAND-5601-D LED moisture-proof luminaire "VASCA"

LED diffuser luminaire, VASCA series, IP65, IK08. Housing made from polycarbonate. Prismatic diffuser made from PC, UV-resistant. Diffuser is fastened with stainless steel clips. LED boards can be interchanged individually. Operating unit can be switched or dimmed (DALI dimmer), installed. Feed-through wiring present. Version with Casambi Bluetooth control available. DC compatible.



DANE TECHNICZNE

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0,95
System power	54 W
DC Ready	Yes
Connection cross section	1,5 mm ²
Communication type	DALI 1
Dimming	DALI
Electrical version	with internal operating device, dimmable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	4 000 K
Rated luminous flux	6 800 lm
Light colour	840
Colour rendering index (CRI)	> 80
Colour tolerance	2
Beam angle	120 °
UGR	24
Lifetime (h, at 25°C)	50 000 h, L80



Acceptance tests	
Certifications	CE, ROHS, EMC
Protection class	I
Ingress protection (IP) rating	IP 65
Impact resistance	IK 08
Glow wire test	850° C
Ambient temperature	-20 to +40 C°
Physical data	
Mounting method	ceiling mounted, wall mounted
Housing material	PC
Cover material	PC
Length (L)	1 560 mm
Width (B)	97 mm
Height (H)	82 mm
Product weight	2,2 kg
Weight incl. Packaging	2,3 kg
Packaging Length (L)	1 585 mm
Packaging Width (B)	100 mm
Packaging Height (H)	90 mm



LIGHT DISTRIBUTION

