



**Art.-No.: YWDLA-LPND-5301-UI**  
**LED pendant luminaire "LARO", c- surface mounting,**  
**direct / indirect distribution, 1122x93x80mm, 53W,**  
**6000lm, 3000K, CRI >80, IP40, UGR <19, Dali dimmable**

LED ceiling- and wall-mounted luminaire, LARO series, with direct and direct/indirect beam. Housing made from aluminium, white, powder-coated. Diffuser made from plastic (PMMA), micro-prismatic, UV-stabilised. Operating unit can be switched or dimmed (DALI dimmer), integrated. UGR < 19 and screen-compliant in accordance with EN 12464-1. Version with CASAMBI Bluetooth control available.



## DANE TECHNICZNE


Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0,98
System power	53 W
Inrush current	20 A
Luminaires on B10A fuse	13 Stk.
Luminaires on B16A fuse	20 Stk.
Luminaires on C10A fuse	20 Stk.
Luminaires on C16A fuse	33 Stk.
Connection cross section	1,5 mm <sup>2</sup>
Dimming	DALI
Electrical version	with internal operating device, dimmable
CASAMBI Ready	Yes



Photometrical data	
Light source	LED
Colour temperature	4 000 K
Rated luminous flux	6 000 lm
Luminous efficacy	113 lm/W
Light colour	840
Colour tolerance	2
Beam angle	68/66 °
UGR	15,5
Lifetime (h, at 25°C)	50 000 h, L80
Acceptance tests	
Certifications	CE
Protection class	I
Ingress protection (IP) rating	IP 40
Glow wire test	650° C
Ambient temperature	0 to +25 C°
Physical data	
Mounting method	pendant fitting
Housing material	Aluminium
Housing colour	white
Cover material	PMMA
Length (L)	1 122 mm
Width (B)	93 mm
Height (H)	80 mm
Product weight	4,7 kg
Weight incl. Packaging	4,9 kg
Packaging Length (L)	1 300 mm
Packaging Width (B)	150 mm
Packaging Height (H)	150 mm



**LIGHT DISTRIBUTION**



cd/klm  
— C0 - C180 — C90 - C270

$\eta = 100\%$