



**Art.-No.: YWDLA-RADT-2901**  
**LED luminaire "LARIO", w-/c- surface mounting, round,**  
**400x66mm, 29W, 2950lm, 3000, 4000, 6000K, Dip-Switch,**  
**CRI >80, IP54, white, Triac**



LED ceiling- and wall-mounted luminaire, LARIO series, IP54. Housing and diffuser made from PC (fire- and UV-resistant), opal. Operating unit integrated (can be switched). Three-stage adjustment of colour temperature (3000K, 4000K, 5700K) using DIP switch. Version with CASAMBI Bluetooth control available.

## TECHNICAL DATA

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0.9
System power	29 W
Dimming	TRIAC
Electrical version	with internal operating device, dimmable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	3000/4000/6000 K
Rated luminous flux	2,950 lm
Luminous efficacy	102 lm/W
Light colour	830/840/860
Colour rendering index (CRI)	> 80
Colour tolerance	3
Beam angle	117 °
UGR	23.9
Lifetime (h, at 25°C)	50,000 h, L80
Acceptance tests	
Certifications	CE, ROHS
Protection class	II
Ingress protection (IP) rating	IP 54
Ambient temperature	-20 to +45 C°



Physical data	
Mounting method	ceiling mounted, wall mounted
Housing material	PC
Housing colour	white
Cover material	PC
Height (H)	66 mm
Diameter $\varnothing$	400 mm
Product weight	1.31 kg
Weight incl. Packaging	1.81 kg



**LIGHT DISTRIBUTION**

