



**Art.-No.: YWDPO-RENS-3301-D**  
**LED luminaire "PORIO", wall / ceiling recessed mounting,**  
**round, 464x125mm, 33W, 3000lm, 4000K, CRI >80, IP20,**  
**white, switchable**

LED ceiling- and wall-mounted luminaire, PORIO series, recessed design, as the basic lighting for commercial and residential rooms. Housing made from steel plate, white, powder-coated. Diffuser made from plastic (PMMA), opal, UV-stabilised. Operating unit can be switched or dimmed (DALI dimmer), integrated. Version with CASAMBI Bluetooth control available. DC compatible.



## DANE TECHNICZNE

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0,95
System power	33 W
Luminaires on B10A fuse	16 Stk.
Luminaires on B16A fuse	27 Stk.
Luminaires on C10A fuse	27 Stk.
Luminaires on C16A fuse	45 Stk.
DC Ready	Yes
Connection cross section	1,5 mm <sup>2</sup>
Electrical version	with internal operating device, switchable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	4 000 K
Rated luminous flux	3 000 lm
Luminous efficacy	91 lm/W
Light colour	840
Colour rendering index (CRI)	> 80
Colour tolerance	3
Beam angle	87,6 °
UGR	20,6
Lifetime (h, at 25°C)	50 000 h, L80



Acceptance tests	
Certifications	CE
Protection class	I
Ingress protection (IP) rating	IP 20
Glow wire test	650° C
Ambient temperature	0 to +25 C°
Physical data	
Mounting method	recessed ceiling mounted
Housing material	Aluminium
Housing colour	white
Cover material	PMMA
Height (H)	90 mm
Diameter ø	464 mm
Product weight	4 kg
Weight incl. Packaging	4,2 kg
Packaging Length (L)	480 mm
Packaging Width (B)	480 mm
Packaging Height (H)	140 mm



**LIGHT DISTRIBUTION**



cd/klm

$\eta = 100\%$

— C0 - C180    — C90 - C270