



Art.-No.: YWDRO-RANS-2601-DS
LED luminaire "RONDA", wall / ceiling surface mounting,
round, 395x108mm, 26W, 2300lm, 4000K, CRI >80, IP20,
silver, switchable

LED ceiling- and wall-mounted luminaire, Ronda series. Housing made from aluminium, silver or white, IP20. Diffuser made from plastic (PMMA), opal, UV-stabilised. Operating unit can be switched, installed. Version with Casambi Bluetooth control available.



DANE TECHNICZNE


Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0,9
System power	26 W
Inrush current	10 A
Luminaires on B10A fuse	40 Stk.
Luminaires on B16A fuse	64 Stk.
DC Ready	Yes
Connection cross section	1,5 mm ²
Electrical version	with internal operating device, switchable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	4 000 K
Rated luminous flux	2 300 lm
Light colour	840
Colour rendering index (CRI)	> 80
Beam angle	120 °
UGR	25,6
Lifetime (h, at 25°C)	50 000 h, L80



Acceptance tests	
Certifications	CE, ROHS
Protection class	II
Ingress protection (IP) rating	IP 20
Impact resistance	IK 02
Ambient temperature	-20 to +40 C°
Storage temperature	-20 to +45 C°
Physical data	
Mounting method	ceiling mounted, wall mounted
Housing material	Aluminium
Housing colour	silver
Height (H)	108 mm
Diameter ø	395 mm
Product weight	1,4 kg
Weight incl. Packaging	1,5 kg
Packaging Length (L)	440 mm
Packaging Width (B)	440 mm
Packaging Height (H)	120 mm



LIGHT DISTRIBUTION



cd/klm

$\eta = 100\%$

— C0 - C180 — C90 - C270