



Art.-No.: YWDZO-LANS-4401-D
LED lamp "ZORRO", wall / ceiling surface mounting,
1100x165x63mm, 44W, 5000lm 4000K, CRI >80, IP40,
switchable



LED ceiling- and wall-mounted luminaire, ZORRO. Housing made from steel plate, white, powder-coated. Diffuser made from plastic (PC), opal, UV-stabilised. Operating unit can be switched or dimmed (DALI dimmer), integrated. Version with CASAMBI® Bluetooth control available. DC compatible. NANO protection on request.

DANE TECHNICZNE

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0,9
System power	44 W
Inrush current	30 A
Inrush current duration	200 µs
Luminaires on C16A fuse	60 Stk.
Connection cross section	2,5 mm ²
Electrical version	with internal operating device, switchable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	4 000 K
Rated luminous flux	5 000 lm
Luminous efficacy	114 lm/W
Light colour	840
Colour rendering index (CRI)	> 80
Colour tolerance	3
Beam angle	90 °
UGR	26,7
Lifetime (h, at 25°C)	75 000 h, L80



Acceptance tests	
Certifications	CE
Protection class	I
Ingress protection (IP) rating	IP 40
Ambient temperature	-20 to +25 C°
Physical data	
Mounting method	ceiling mounted
Housing material	Steel sheet
Housing colour	white
Cover material	PC
Length (L)	1 100 mm
Width (B)	165 mm
Height (H)	63 mm
Product weight	2,2 kg
Weight incl. Packaging	2,5 kg
Packaging Length (L)	1 313 mm
Packaging Width (B)	166 mm
Packaging Height (H)	57 mm



LIGHT DISTRIBUTION

