



## Emergency luminaire Art.-No.: ZAW018SC-AZ

Robust wall-mounted Zinc die-cast luminaire for the lighting of escape and rescue routes in exit areas according to DIN EN 60598-1, DIN EN 60598-2-22 and EN 1838. Appealing design with concealed screws.

Available for central power systems or as a LED self-contained emergency luminaire.



### TECHNICAL DATA

Luminaire type	Emergency luminaire
Mounting	Wall mounted
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast
Colour	RAL 7016
Mechanical rating IP	65
Impact resistance IK	8
Protection class	1
Supply	Single battery
Monitoring	Self-Control
Operation time	8 h
Battery	3.2V / 3.3 Ah LiFePO4
Operation mode	maintained/non-maintained mode
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Input Voltage DC	- V
Power consumption max.	4,6 W
Power consumption maintained	3,3 W
Power consumption non-maintained	1 W
Ambient temperature maintained mode	-5 °C / 35 °C
Ambient temperature non-maintained mode	-5 °C / 40 °C
Length	65 mm
Width	315 mm



Height	140 mm
Weight	2.1 kg
Weight incl. Packaging	2.22 kg
Connection cross-section	2.5 mm
Switching input L'	Yes
Emergency light blocking	No
Battery connector	Plug
Dimming function	No
Luminous flux mains mode	190 lm
Luminous flux emergency mode	85 lm
Customs tariff number	94056180
Country of origin	Germany
EAN	4260682140920

## TECHNICAL DRAWING

